



RIG #5

Rated Drill Depth	:	20,000 ft
Drawworks	:	Dreco Electric 2000 HP
Mast	:	Dreco 147' 1,125,000 lbs GNC Hook Load Capacity 12 Lines : 1.125.000 lbs Hook Load Capacity 10 Lines : 1.070.000 lbs
Substructure	:	Dreco, Self Elevating Sling Shot System Casing Load Rating : 1.250.000 lbs Set Back Capacity : 750,000 lbs
Skidding	:	Skidding Package (available)
Engines	:	Four (4) Cat D-399 TA, 1215 HP each
Generators	:	Three (3) CAT SR4 x AC 1,050 KW each One (1) AC KATO 1,200 RPM 1050 KW
SCR System	:	Integrated Power System Model 1291, 3 phase, 600 V, 2650 KVA
Rotary Table	:	Oilwell, 37-1/2" Independent drive, 1000 HP, GE Motor
Clear height below RT Beam to GL	:	24 ft
Hoisting Equipment	:	500 tons
Top Drive	:	Varco TDS-11S 500T
Pumps	:	Three (3) National 10P-130 @ 1300 HP each Powered by 2 ea GE 752, 1,000 HP DC Motor on each pump
BOP Equipment	:	29 1/2" x 500 psi Diverter system 13 5/8" x 10,000 psi single ram (3 unit) + Annular 13 5/8" – 10,000 psi 20 3/4" x 3,000 psi single ram (2 unit) + Annular 21 1/4" – 2,000 psi
Mud Tank System	:	2500 bbls mud system
Solid Control	:	Four (4) Shale Shaker Derrick 4 Panel Hyperpool 10 x Cones Desilter 2 x Cones Desander
Drill Pipe	:	5" Drill Pipe String
Camp	:	200 persons
Transportation	:	2 x 50 ton Crawler Crane 2 x 5 ton Forklift Cat 950

PT Apexindo Pratama Duta Tbk

Head Office : Office 8 20th – 21st Floor, SCBD Lot 28 JL. Jend. Sudirman Kav. 52-53 , Jakarta 12190
Tel. (62-21)29333000 , 29333020 (Hunting) Fax. (62-21) 29333111
Email: info@apexindo.com

Branch Office : Jl. Jend. Sudirman, Balikpapan Permai Complex, Blok L No. 10-12, Balikpapan 76114
Tel. (62-542) 410 258 (Hunting) Fax. (62-542) 411 788

Contact Person : Donald Kent Wood (Director/ Independent Director)

www.apexindo.com